



NOTES:

- CONNECT +5V DC TO J3 AS SHOWN ON SILK-SCREEN.
- J3 IS SUITABLY PROTECTED TO FROM ERRANT CONNECTIONS, HOWEVER VOLTAGES ABOVE 24V WILL DAMAGE THE DEVICE.
- SEE DRAWING CDPDIFC21119 FOR DETAILS ON SERIAL PORT ADAPTER CABLE FOR CONNECTING J2 TO ANY DTE DEVICE.
- CUSTOM CABLE AVAILABLE UPON REQUEST
- SW1 IS A RESET SWITCH, AND IS INTENDED FOR USE IN TESTING AND CONFIGURING INSTALLATIONS.
- MOUNTING HOLES ARE SIZED FOR #4 MOUNTING SCREWS.
- ALL STAND-OFFS AND SCREWS FOR MOUNTING SB300 MODEM ARE PROVIDED.

TOLERANCES UNLESS OTHERWISE SPECIFIED	
0.XXX	+/- 0.003 IN
0.XX	+/- 0.005 IN
0.X	+/- 0.010 IN

DRAWN:	L. JOHNSON
CHECKED:	L. JOHNSON
APPROVED:	L. JOHNSON

PART No.	N/A
DWG No.	CDPDC31121

REV.	1.0
SIZE:	A

TITLE: CDPD CARRIER BOARD	
SHEET 1 OF 1	DATE: 11.21.2003